



The Neto Colorflex 18-IPX is a durable and cost-effective tool for lighting designers. With powerful RGBAW+UV internal colour mixing and a 25 degree output, the Colorflex 18-IPX is versatile for use in applications such as Touring, Rental, Permanent Installation, Architectural Lighting and more.

### POWER

Input Voltage : 90-240V AC 60/50Hz  
 Consumption : 200W  
 Lamp type : 18x15W LED  
 - Seetronic True1 Power Input + Link Output (IP65)  
 Connections :  
 - Seetronic XLR 3-pin or 5-pin Input + Link Output (IP65)

### PHYSICAL

Size : 310 x 310 x110 mm  
 Weight : 7.3 kg  
 Display : LCD display with 4-button control  
 IP Rating : N/A

### CONTROL

Control : DMX, Stand-Alone  
 Input : 3 or 5 pin XLR (DMX)  
 DMX Footprint : HSV(3ch), HSI(3ch), 6ch, 8ch, 12ch  
 Dimming : Variable Refresh Rate Electronic Dimmer (800HZ, 2000HZ, 4000HZ, 10KHZ, 20KHZ, 25KHZ)  
 Color : 6-in-1 RGBWA+UV Internal Color Mixing  
 Movement : N/A

### OPTICS

Beam Angle : 25° Standard, 15° available  
 Focus : Soft Edge Beam / Flood  
 Filters : N/A